

CONICAL VALVE SPRING KITS

Part Number	Installed Height	Installed Pressure	Pressure @ .5 Lift	Max. Lift	Solid Height	Spring Retainer	Valve Locks
FORD BA 6 CYLINDER INCLUDES SPRINGS AND RETAINERS. LOCKS NOT INCLUDED							
VTKBA6T-24	1.520"	105	205	.570"	.900"	10703-24	Std
FORD BA V8 XR8 TO MAY 2008 INCLUDES SPRINGS AND RETAINERS. LOCKS NOT INCLUDED							
VTKBAXR8-32	1.520"	105	205	.570"	.900"	10704-32	Std
HOLDEN ECOTEC V6 INCLUDES SPRINGS, RETAINERS AND LOCKS							
VTK-ECOTEC	1.780"	120	270	.550"	1.100"	10707-12	10701-12
VTK-ECOTEC/R	1.780"	150	310	.580"	1.100"	10707-12	10701-12
FORD CLEVELAND V8 302-351 CONICAL SPRING KIT SINGLE GROOVE VALVE ONLY INCLUDES SPRINGS, RETAINERS AND LOCKS							
VTKCS84	1.920"	140	310	.600"	1.220"	11709-16	4134-16
HOLDEN 6 VP-VR INCLUDES SPRINGS AND RETAINERS. LOCKS NOT INCLUDED							
VTKCS61	1.725"	125	275	.550"	1.100"	11708-12	Stock
HOLDEN V8 304-308 CONICAL SPRING KIT NOTE: ENGINE NEEDS TO BE FITTED WITH POSITIVE STEM SEALS. SPECIAL FITTING REQUIRED. PLEASE CONTACT CROW CAMS TECHNICAL DEPARTMENT BEFORE FITTING. INCLUDES SPRINGS, RETAINERS AND LOCKS							
VTKCS83	1.800"	135	305	.600"	1.125"	11708-16	4133-16
VTKCS83A	1.850"	115	300	.600"	1.125"	11708-16	4134-16

VALVE SPRING & RETAINER KITS

Part Number	Installed Height	Installed Pressure	Pressure @ .5 Lift	Max. Lift	Spring Seat	Spring	Spring Retainer	Valve Locks
FORD 6 CYL AU SPRING KITS DUAL SPRINGS MEASURED WITH RETAINER INCLUDES SPRINGS AND RETAINERS. LOCKS NOT INCLUDED. DUAL SPRINGS REQUIRE HEAD MACHINING TO FIT.								
VTKAU³	1.820"	98	255	.650"	VSS1456	<u>7332-12</u> ^D	11740-12	Stock
VTKAU-S³	1.820"	100	270	.600"	Std	7739-12	11750-12	Stock
VTKAU-R³	1.820"	124	285	.650"	VSS1456	<u>7333-12</u> ^D	11740-12	Stock
FORD COYOTE V8 MUSTANG SPRING KIT INCLUDES SPRINGS AND TITANIUM RETAINERS. LOCKS NOT INCLUDED								
Part Number	Installed Height	Installed Pressure	Pressure @ .5 Lift	Max. Lift	Coil Bind	Spring	Spring Retainer	Valve Locks
VTKCOYOTE	1.575"	92 @ 1.550"	218 @ 1.050"	.575"	0.941"		Titanium Retainers	Standard
TOYOTA LANDCRUISER 1FZ-FE SINGLE SPRING KIT INCLUDES SPRINGS AND RETAINERS. LOCKS NOT INCLUDED								
VTK4163	1.487"	105	235	.462"	0.93"	4163	10715	Stock
NISSAN PATROL TB48 SINGLE SPRING KIT INCLUDES SPRINGS AND RETAINERS. LOCKS NOT INCLUDED								
VTK4162	1.550"	90	230	0.550"	0.94"	4162	10716	Std
HOLDEN V8 LS1, LS2, LS7 SINGLE SPRING KITS INCLUDES SPRINGS, RETAINERS, LOCKS, STEM SEALS AND SHIMS.								
VTKLS1	1.780"	120	270	.550"	1.100"	4231-16	10707-16	10701
VTKLS5	1.780"	140	330	.600"	1.100"	1511ML-16	10707-16	10701
HOLDEN V8 LS1, LS2, LS7 DOUBLE SPRING KIT INCLUDES SPRINGS, RETAINERS, LOCKS, STEM SEALS AND SHIMS. DUAL SPRINGS MEASURED WITH RETAINER.								
VTKLS8	1.780"	165	340	.650"	1.000"	<u>4438-16</u> ^D	10708-16	10701
VTKLST	1.800"	165	360	.650"	1.020"	<u>4439-16</u> ^D	Included Titanium	Included
VTKLS9	1.800"	165	360	.650"	1.020"	<u>4439-16</u> ^D	10708-16	10701
CROW MT VALVE SPRING KITS DUAL SPRINGS MEASURED WITH RETAINER. SUITABLE FOR MILD FORD AND HOLDEN HYDRAULIC APPLICATIONS.								
MT173K	1.625"	90	190	0.645"	0.930"	MT173	MTR186	11703
MT186K	1.625"	120	250	0.615"	0.960"	MT186	MTR186	11703
MT192K	1.660"	115	260	0.670"	0.940"	<u>MT192</u> ^D	MTR186	11703
MT202K	1.500"	110	205	0.540"	0.880"	MT202	MTR186	11703
MT250K	1.880"	100	255	0.600"	1.180"	MT250	MTR250Z	11704
MT250KR	1.820"	100	255	0.600"	1.180"	MT357	MTR250	11704
MT302K	1.700"	110	275	0.535"	1.100"	MT302	MTR302	11701
MT308K	1.700"	115	285	0.570"	1.080"	MT308	MTR308	11701
MT350K	1.700"	120	320	0.490"	1.160"	MT350	MTR308	11701
MT357K	1.820"	110	280	0.600"	1.180"	MT357	MTR351	11702
MT6005K	1.800"	140	300	0.700"	1.050"	<u>MT6005</u> ^D	MTR333	11701

Note: Springs marked with xxxx-xx^D denotes that it is a double spring.