

FORD BIG BLOCK V8

Parts Kit includes items marked in black to suit selected camshaft

Application	RPM Range	Part No.	Adv. Duration		.050" Duration		Valve Lift		Lash Intake	Lash Exhaust	Lobe L/C	Parts Kit	Lifters	Valve Spring	Retainer	Locks	Stem Seal	Timing Kit	Pushrods	Rockers
			Intake	Exhaust	Intake	Exhaust	Intake	Exhaust												
FE, 332, 352, 390, 406, 427, 428 HYDRAULIC																				
Maximum low end torque, dual pattern suit LPG needs valve springs & exhaust (See Fitting notes 1, 2, 3 & 4)	1500 - 4500	19666	270	280	204	214	.484"	.510'				112	K1901	HT950	7738	12700-16	12708		CS8FE428	
Mild street applicaton, medium idle good mid range, needs valve springs etc (See Fitting notes 1, 2, 3 & 4)	2000 - 5000	19665	280	290	214	224	.512"	.538"				112	K1902	HT950	7333	12700-16	12708		CS8FE428	
Hot street cam, strong mid range needs headers, carbie, hi- stall etc & rockers (See Fitting notes 1, 2, 3 & 4)	2200 - 5700	191367	286	293	224	234	.535"	.560"				112	K1902	HT950	7333	12700-16	12708		CS8FE428	
Street /strip cam, aggressive idle needs heads, carbie headers & hi stall (See Fitting notes 1, 2, 3 & 4)	2600 - 6300	19787	290	310	238	246	.560"	.564"				109	K1902	HT950	7333	12700-16	12708		CS8FE428	
Street/strip application rough idle needs heads, carbie, headers, hi stall & rockers (See Fitting notes 1, 2, 3 & 4)	3200 - 6300	19700	304	316	242	250	.570"	.570"				108	K1902	HT950	7333	12700-16	12708		CS8FE428	

FORD OHC 6

EA-EL 1989 - JAN 98 MULTIPOINT EFI																				
High torque cam to suit EA-ED multi point can use as STD replacement	900 - 3500	222002	242	240	194	194	.470"	.454'				114			7739-12	12700-12	11704		CS6EA-VS	
Mild performance cam, EA-ED multi point suit STD computer needs headers	1000 - 4200	222825	265	260	196	196	.489"	.489"				113			7739-12	12700-12	11704		CS6EA-VS	
Mild performance cam, EF-EL suit STD computer needs headers & valve springs	1200 - 4700	2222519	262	258	198	198	.494"	.472"				113			7739-12	12700-12	11704		CS6EA-VS	
Medium performance cam needs computer mods headers & valve springs	1500 - 5200	2222549	268	260	210	200	.530"	.500"				112			7739-12	12700-12	11704		CS6EA-VS	
EL-AU FEB 98-02																				
High torque cam to suit AU series 1 can use with LPG - NON VCT	900 - 4500	2232526	265	265	197	197	.476"	.454"				115			7739-12	11740-12			CS6EA-VS	
High torque cam to suit AU series 11 can use with LPG - NON VCT	900 - 4500	2232522	265	260	201	194	.484"	.459"				115			7739-12	11740-12			CS6EA-VS	
Medium performance cam needs computer mods headers & valve springs	1500 - 5200	2232549	268	260	210	200	.476"	.450"				112			7739-12	11740-12			CS6EA-VS	
Performance street/strip cam lopey idle needs valve springs headers & computer	2500 - 5800	2231514	275	275	219	219	.504"	.504"				112			7739-12	11740-12			CS6EA-VS	

FITTING NOTES: 1. Must use performance springs. 2. Must use performance retainers. 3. Machining required to fit these components. 4. Must use performance seal. 5. Notes 1 to 4 all apply to this part number. 6. Check valve train geometry before ordering pushrod. 7. Pushrod length varied in this model. Check length before ordering 8. Spring height varies in models check pressure before installation.

FITTING NOTES:
 • Converter stall speed should be equal to or greater than the minimum rpm of the cam power range.
 • All lash settings quoted are measured hot. • The use of high volume oil pumps may cause premature wear of the distributor gear.