

# CHEV/HOLDEN LS V8 3 BOLT

Parts Kit includes items marked in black to suit selected camshaft

Application	RPM Range	Part No.	Adv. Duration		.050" Duration		Valve Lift		Lash Intake	Lash Exhaust	Lobe L/C	Parts Kit	Lifters	Valve Spring	Retainer	Locks	Stem Seal	Timing Kit	Pushrods	Rockers
			Intake	Exhaust	Intake	Exhaust	Intake	Exhaust												
<b>SUPERCHARGED &amp; TURBO</b>																				
Supercharged street cam great power & torque through wide RPM range (See Fitting notes 1, 2 & 4)	2200 - 6500	871292	276	296	225	244	.606"	.606"			115	K872	5251	4438	10708	10702	S9-16	See Notes	PR5740	
Supercharged street cam with great mid range power (See Fitting notes 1, 2 & 4)	2600 - 6900	871293	291	301	235	251	.590"	.608"			114	K872	5251	4438	10708	10702	S9-16	See Notes	PR5740	
Streetable supercharged cam wide torque & power range (See Fitting notes 1, 2 & 4)	2800 - 7000	871294	293	295	239	242	.585"	.590"			115	K872	5251	4438	10708	10702	S9-16	See Notes	PR5740	
Street/strip turbo cam wide power & torque range (See Fitting notes 1, 2 & 4)	2700 - 6900	871295	285	280	231	225	.602"	.608"			114	K872	5251	4438	10708	10702	S9-16	See Notes	PR5740	
Street/ Race turbo cam very strong mid range & top end power (See Fitting notes 1, 2 & 4)	2600 - 7000	871296R	290	286	237	232	.603"	.605"			115	K872	5251	4438	10708	10702	S9-16	See Notes	PR5740	

# NISSAN/HOLDEN

<b>RB30 SOHC 1986-1997</b>																				
Stock replacement cam for normally aspirated	1500 - 5000	503000	256	255	195	191	.375"	.375"			110			5840-12				CS6RB30-V		
Stock replacement for TURBO engine	1500 - 5000	503001	256	255	195	191	.375"	.375"			117			5833-12				CS6RB30-V		
Mild cam for normally aspirated engine	2000 - 5800	503NA	250	250	194	194	.426"	.426"			110			5833-12				CS6RB30-V		
Mild performance cam for stock or near stock boost	2200 - 6200	503TX1	265	271	205	209	.437"	.450"			117			5833-12				CS6RB30-V		
Meduim street performance turbo cam	2500 - 6500	503TXM	280	280	214	214	.470"	.470"			117			5833-12				CS6RB30-V		
Street / strip TURBO cam	3000 - 7000	503TX2	292	292	230	230	.483"	.483"			117			5833-12				CS6RB30-V		



**NOTE: GM LS Chain sets not supplied in Parts Kit. Order by engine type below.**

Engine	Chain Set Single Row	Chain Set Double Row	Engine	Chain Set Single Row	Chain Set Double Row
LS1,LS6 5.7L 3 bolt cam	CS8LS1-SR	CS8LS1	LS3,L76, L98 6.0 L Single bolt cam Not AFM	CS8L98	
LS2 6.0L 3 bolt cam	CS8LS2-SR	CS8LS2	L76, L98 3 bolt cam conversion	CS8LS7-SR	CS8LS7
LS7 7 litre 3 bolt cam	CS8LS7-SR	CS8LS7	3 bolt cam gear only	CS8LS-VE3	

### FITTING NOTES:

- Converter stall speed should be equal to or greater than the minimum rpm of the cam power range.
- All lash settings quoted are measured hot.
- The use of high volume oil pumps may cause premature wear of the distributor gear.

- FITTING NOTES:** 1. Must use performance springs. 2. Must use performance retainers. 3. Machining required to fit these components. 4. Must use performance seal. 5. Notes 1 to 4 all apply to this part number. 6. Check valve train geometry before ordering pushrod. 7. Pushrod length varied in this model. Check length before ordering 8. Spring height varies in models check pressure before installation.