

FORD BA D.O.H.C 6 cyl

Ford BA 6 cyl 24 valve						
PART NO.		ADV DUR	0.050" DUR.	VALVE LIFT	POWER RANGE	COMMENTS
3231393	Inlet	259	195	0.454"	1000	Medium profile. Suit normally aspirated and turbo applications.
3241393	Exhaust	259	195	0.454"	4500	
3232565	Inlet	300	236	0.510"	3000	Race profile for circuit or speedway applications.
3242565	Exhaust	300	236	0.510"	6000	
323900	Custom ground inlet.					
324900	Custom ground exhaust.					

Ford BA 6 DOHC Valve Springs Turbo & Normally Aspirated							
PART NO.	INST. HEIGHT	INST. PRESSURE	PRESSURE @.5 LIFT	MAX LIFT	SOLID HEIGHT	SPRING RETAINER	VALVE LOCKS
1 8 0 8 - 2 4	1.48"	90	195	0.55"	0.90"	Std	Std
1 8 0 9 - 2 4	1.48"	115	225	0.55"	0.90"	Std	Std
VTKBA6-24	1.52"	105	205	0.60"	0.89"	10703	Std

Performance Valve Train Components			
PART NO	DESCRIPTION	PART NO	DESCRIPTION
VTKBA6T-24	Spring & Retainer kit BA 6 cyl	10703-24	+0.040" retainers suit 6 cyl
1808-24	Perform. Valve spring set BA 6 cyl	BA-ADJ	Hydraulic Tappet Lash Adjuster
1809-24	Race Valve spring set BA 6 cyl		

NOTE. Check for rocker to retainer clearance when fitting offset retainers.