

# FORD BA D.O.H.C 6 cyl

## **Ford BA 6 cyl 24 valve. These camshafts all require tuning.**

<b>PART NO.</b>		<b>ADV DUR</b>	<b>0.050" DUR.</b>	<b>VALVE LIFT</b>	<b>POWER RANGE</b>	<b>COMMENTS</b>
<b>3231393</b>	Inlet	259	195	0.454"	1000	Mild profile. Suit normally aspirated and turbo applications.
<b>3241393</b>	Exhaust	259	195	0.454"	4500	
<b>3232562</b>	Inlet	282	212	0.500"	1500	Medium profile. Suit normally aspirated applications.
<b>3242562</b>	Exhaust	282	209	0.500"	5000	
<b>3232565</b>	Inlet	300	236	0.510"	3000	Race profile for circuit or speedway applications.
<b>3242565</b>	Exhaust	300	236	0.510"	6000	
<b>323900</b>	Custom ground inlet.					
<b>324900</b>	Custom ground exhaust.					

## **Ford BA 6 DOHC Valve Springs Turbo & Normally Aspirated**

<b>PART NO.</b>	<b>INST. HEIGHT</b>	<b>INST. PRESSURE</b>	<b>PRESSURE @.5 LIFT</b>	<b>MAX LIFT</b>	<b>SOLID HEIGHT</b>	<b>SPRING RETAINER</b>	<b>VALVE LOCKS</b>
<b>1 8 0 8 - 2 4</b>	1.48"	90	195	0.55"	0.90"	Std	Std
<b>1 8 0 9 - 2 4</b>	1.48"	115	225	0.55"	0.90"	Std	Std
<b>VTKBA6-24</b>	1.52"	105	205	0.60"	0.89"	10703	Std

## **Performance Valve Train Components**

<b>PART NO</b>	<b>DESCRIPTION</b>	<b>PART NO</b>	<b>DESCRIPTION</b>
<b>VTKBA6T-24</b>	Spring & Retainer kit BA 6 cyl	<b>10703-24</b>	+0.040" retainers suit 6 cyl
<b>1808-24</b>	Perform. Valve spring set BA 6 cyl	<b>BA-ADJ</b>	Hydraulic Tappet Lash Adjuster
<b>1809-24</b>	Race Valve spring set BA 6 cyl		

**NOTE.** Check for rocker to retainer clearance when fitting offset retainers.