

<b>Datsun L Series 4 Cylinder Engines 1600,1800, 2000 1969-80</b>							
<b>PART NO.</b>	<b>VALVE TIMING</b>	<b>DUR</b>	<b>.075" DUR.</b>	<b>L/C</b>	<b>VALVE LIFT</b>	<b>POWER RANGE</b>	<b>COMMENTS</b>
<b>30643</b>	IN. 40/75 EX.74/38	295 292	212 210	108	.480" .495"	2000 5800	High torque cam for stock engines.
<b>30640</b>	IN. 40/76 EX.77/41	296 298	214 216	108	.485" .495"	2200 6200	Mild performance cam for stock/near stock engines.
<b>30721</b>	IN. 39/73 EX.75/37	292 292	225 225	108	.495" .495"	3000 6500	Medium street performance cam.
<b>30832<sup>1</sup></b>	IN. 37/65 EX.69/33	282 282	232 232	106	.498" .498"	3500 7000	Hot cam for street/race applications.
<b>30900</b>	Custom ground billet using one master.						

<b>Datsun 6 Cylinder L Series Engines 2400,2600,2800 1969-83</b>							
<b>PART NO.</b>	<b>VALVE TIMING</b>	<b>DUR</b>	<b>.075" DUR.</b>	<b>L/C</b>	<b>VALVE LIFT</b>	<b>POWER RANGE</b>	<b>COMMENTS</b>
<b>58640</b>	IN. 40/76 EX.77/41	296 298	214 216	108	.485" .495"	2200 6200	Mild cam for use in stock or near stock engines
<b>58900</b>	Custom ground billet using one master.						

<b>Nissan SR20 Pulsar, 200SX, 1998cc 1992-2003 Hydraulic Lifters</b>							
<b>PART NO.</b>	<b>VALVE TIMING</b>	<b>DUR</b>	<b>.050" DUR.</b>	<b>VALVE LIFT</b>	<b>POWER RANGE</b>	<b>COMMENTS</b>	
<b>5302559</b>	Inlet	288	192	.370"	2200	Mild performance cams Suits VCT and non VCT	
<b>5022559</b>	Exhaust	285	192	.370"	6200		
<b>5302553</b>	Inlet	295	220	.410"	3500	High performance cams Suits VCT and non VCT	
<b>5022553</b>	Exhaust	295	220	.410"	7500		
<b>530900</b>	Custom ground billet Inlet						
<b>503900</b>	Custom ground billet exhaust.						

<b>Nissan RB26 Skyline Solid Lifters</b>							
<b>PART NO.</b>	<b>VALVE TIMING</b>	<b>DUR</b>	<b>.050" DUR.</b>	<b>VALVE LIFT</b>	<b>POWER RANGE</b>	<b>COMMENTS</b>	
<b>35361587</b>	Inlet	268	219	.361"	2200	Medium performance cams Suits VCT and non VCT	
<b>35371587</b>	Exhaust	268	219	.361"	6200		
<b>35361377</b>	Inlet	280	227	.380"	2500	High performance cams Suits VCT and non VCT	
<b>35371377</b>	Exhaust	280	227	.380"	6800		
<b>353690</b>	Custom ground billet Inlet						
<b>353790</b>	Custom ground billet exhaust.						

**NOTES.** 1. Must use performance valve springs