

Datsun L Series 4 Cylinder Engines 1600,1800, 2000 1969-80							
PART NO.	VALVE TIMING	DUR	.075" DUR.	L/C	VALVE LIFT	POWER RANGE	COMMENTS
30643	IN. 40/75 EX.74/38	295 292	212 210	108	.480" .495"	2000 5800	High torque cam for stock engines.
30640	IN. 40/76 EX.77/41	296 298	214 216	108	.485" .495"	2200 6200	Mild performance cam for stock/near stock engines.
30721	IN. 39/73 EX.75/37	292 292	225 225	108	.495" .495"	3000 6500	Medium street performance cam.
30832¹	IN. 37/65 EX.69/33	282 282	232 232	106	.498" .498"	3500 7000	Hot cam for street/race applications.
30900	Custom ground billet using one master.						
30901	Custom ground billet using two masters or modified lobe centres.						

Datsun 6 Cylinder L Series Engines 2400,2600,2800 1969-83							
PART NO.	VALVE TIMING	DUR	.075" DUR.	L/C	VALVE LIFT	POWER RANGE	COMMENTS
58640	IN. 40/76 EX.77/41	296 298	214 216	108	.485" .495"	2200 6200	Mild cam for use in stock or near stock engines
58721	IN. 39/73 EX.75/37	292 292	225 225	108	.495" .495"	3000 6500	Medium street performance cam.
58900	Custom ground billet using one master.						
58901	Custom ground billet using two masters or modified lobe centres.						

Datsun Z20, Z22, Z24 1952-2389cc 1973-89							
PART NO.	VALVE TIMING	DUR	.075" DUR.	L/C	VALVE LIFT	POWER RANGE	COMMENTS
127643	IN. 40/75 EX.74/38	295 292	212 210	108	.480" .495"	1700 5500	High torque cam for near stock engines.
127640	IN. 40/76 EX.77/41	296 298	214 216	108	.485" .495"	2200 6200	Mild cam for use in stock or near stock engines
127900	Custom ground billet.						

Nissan SR20 Pulsar, 200SX, 1998cc 1992-2003 Hydraulic Lifters							
PART NO.	VALVE TIMING	DUR	.050" DUR.	VALVE LIFT	POWER RANGE	COMMENTS	
5302559	Inlet	288	192	.370"	2200	Mild performance cams Suits VCT and non VCT	
5022559	Exhaust	285	192	.370"	6200		
5302553	Inlet	290	220	.410"	3500	High performance cams Suits VCT and non VCT	
5022553	Exhaust	290	220	.410"	7500		
530900	Custom ground billet Inlet						
503900	Custom ground billet exhaust.						

Nissan RB26 Skyline Solid Lifters							
PART NO.	VALVE TIMING	DUR	.050" DUR.	VALVE LIFT	POWER RANGE	COMMENTS	
35361587	Inlet	268	219	.361"	2200	Medium performance cams Suits VCT and non VCT	
35371587	Exhaust	268	219	.361"	6200		
35361377	Inlet	280	227	.380"	2500	High performance cams Suits VCT and non VCT	
35371377	Exhaust	280	227	.380"	6800		
353690	Custom ground billet Inlet						
353790	Custom ground billet exhaust.						

NOTES. 1. Must use performance valve springs