

CONICAL VALVE SPRING KITS

Ford BA 6 Cylinder							
PART NO.	INSTALLED HEIGHT	INSTALLED PRESSURE	PRESSURE @.5 LIFT	MAX. LIFT	SOLID HEIGHT	SPRING RETAINER	VALVE LOCKS
1808-24	1.480"	90	195	0.550"	0.90"	Std	Std
VTKBA6T-24	1.520"	105	205	0.600"	0.90"	10703	Std

Ford BA V8 XR8 to May 2008							
PART NO.	INSTALLED HEIGHT	INSTALLED PRESSURE	PRESSURE @.5 LIFT	MAX. LIFT	SOLID HEIGHT	SPRING RETAINER	VALVE LOCKS
1808-32	1.490"	85	190	0.550"	0.90"	Std	Std

Ford BA V8 XR8 from May 2008							
PART NO.	INSTALLED HEIGHT	INSTALLED PRESSURE	PRESSURE @.5 LIFT	MAX. LIFT	SOLID HEIGHT	SPRING RETAINER	VALVE LOCKS
1809-32	1.590"	95	190	0.600"	0.90"	Std	Std

Holden Ecotec V6							
PART NO.	INSTALLED HEIGHT	SEAT PRESSURE	PRESSURE @.5 LIFT	MAX. LIFT	SPRING SEAT	SPRING RETAINER	VALVE LOCKS
VTK ECOTEC	1.710"	130	280	.530"		10707	10701

RetroFit Conical Spring and Retainer Kits

Holden V8 304-308 Conical Spring kit.							
<i>NOTE Engine needs to be fitted with positive stem seals</i>							
PART NO.	INSTALLED HEIGHT	INSTALLED PRESSURE	PRESSURE @.5 LIFT	MAX. LIFT	SOLID HEIGHT	SPRING RETAINER	VALVE LOCKS
VTKCS81	1.800"	90	245	.520"	1.125"	11709	Stock
VTKCS83A	1.850"	115	305	.600"	1.125"	11709	4134
VTKCS83	1.800"	130	310	.600"	1.125"	11709	4133

Ford Cleveland V8 302-351 Conical Spring kit (single groove valve only)							
PART NO.	INSTALLED HEIGHT	INSTALLED PRESSURE	PRESSURE @.5 LIFT	MAX. LIFT	SOLID HEIGHT	SPRING RETAINER	VALVE LOCKS
VTKCS84	1.930"	140	310	.600"	1.220"	11709	4134
VTKCS85	1.880"	160	330	.600"	1.220"	11709	4133

Holden 6 149-202							
PART NO.	INSTALLED HEIGHT	INSTALLED PRESSURE	PRESSURE @.5 LIFT	MAX. LIFT	SOLID HEIGHT	SPRING RETAINER	VALVE LOCKS
VTKCS61	1.725"	125	275	.550"	1.120"	11709	Stock

Holden 6 VP-VR							
PART NO.	INSTALLED HEIGHT	INSTALLED PRESSURE	PRESSURE @.5 LIFT	MAX. LIFT	SOLID HEIGHT	SPRING RETAINER	VALVE LOCKS
VTKCS61	1.725"	125	275	.550"	1.120"	11709	Stock