

CROW CAMS VALVE SPRINGS Part Number Order

PART NUMBER	O/D	ID OF OUTER	ID OF INNER	SPRING TYPE	RH or LH (OUTER)	FREE LENGTH	SPRING RATE	SOLID HEIGHT
0507	1.000"	0.760"		1	L	2.050"	75	0.900"
1845	1.010"	0.735"	0.518"	2	R	1.800"	245	0.810"
0509	1.060"	0.804"		1	L	1.900"	100	0.760"
0511	0.937"	0.697"		1	L	1.490"	123	0.720"
0512	0.838"	0.612"		1	L	1.500"	125	0.750"
0513	0.953"	0.697"		1	L	1.937"	132	0.870"
0514	0.838"	0.612"		1	L	1.500"	140	0.710"
0515	1.015"	0.730"		1	L	1.950"	140	0.900"
0607	0.910"	0.684"		1	L	1.970"	77	0.750"
0612	1.080"	0.810"		1	R	1.937"	126	0.820"
0613	1.080"	0.796"		1	R	2.230"	130	0.950"
0614	0.970"	0.700"		1	R	2.090"	135	1.030"
1809	1.060"	0.654"		1 Conical	R	1.950"	210	0.885"
minor	0.966"	0.747"		Ovate Wire				
1824	0.983"	0.757"	0.539"	2	R	1.480"	223	0.593"
1824-i	0.725"	0.539"		1	L	1.480"	100	0.589"
1830	0.960"	0.703"	0.518"	2	R	1.680"	293	0.858"
2021	1.134"	0.838"		1	R	1.622"	208	0.800"
2045	1.010"	0.735"		1	R	1.765"	148	0.810"
2834	1.134"	0.838"	0.612"	2	R	1.622"	320	0.800"
2836	1.134"	0.838"	0.612"	2	R	1.622"	340	0.800"
4028	1.275"	0.975"		1	L	1.780"	280	0.820"
4220	1.210"	0.926"	0.693"	2	R	1.900"	200	0.820"
4231	1.275"	0.874"		1 Conical	R	2.180"	295	1.090"
Minor	1.051"	0.650"		Ovate Wire				
4235	1.290"	0.885"		1 Conical	R	2.200"	300	1.080"
Minor	1.050"	0.650"		Ovate Wire				
4224	1.261"	0.965"	0.739"	2	R	1.850"	240	0.780"
4250	1.214"	0.926"	0.693"	2	R	1.900"	243	0.817"
4320	1.255"	0.931"		1	L	2.140"	180	0.900"
4325	1.200"	0.916"	0.705"	2	R	1.490"	270	0.620"
4326	1.255"	0.930"	0.710"	2	L	2.125"	260	0.865"
4327	1.255"	0.930"	0.684"	2	L	2.135"	275	0.930"
4330	1.280"	0.926"	0.700"	2	R	1.690"	315	0.925"
4334	1.280"	0.950"	0.710"	2	L	2.080"	340	0.950"
4335	1.280"	0.950"	0.684"	2	L	2.030"	355	0.950"
4336	1.275"	0.975"	0.700"	2	L	1.780"	360	0.820"
4337	1.275"	0.921"	0.684"	2	L	2.170"	354	1.025"
4338	1.280"	1.054"	0.684"	2	L	2.250"	369	1.030"
4437	1.275"	0.950"	0.684"	2	L	1.780"	374	0.875"
4438	1.295"	0.948"	0.675"	2	R	2.220"	377	1.025"
4719	1.255"	0.930"	0.800"	1 + damper	L	2.135"	220	0.930"
4823	1.282"	0.950"	0.809"	1 + damper	L	2.160"	260	0.930"
4828	1.275"	0.920"		1	L	2.120"	260	0.995"
4830	1.220"	0.860"		1+damper	R	2.080"	310	1.100"
4833	1.250"	0.876"	0.750"	1 + damper	L	1.940"	400	1.010"
4843	1.250"		0.860"	1 + damper	R	2.070"	405	1.160"
4845	1.250"	0.868"	0.787"	1 + damper	R	2.110"	375	1.040"
4918	1.290"	0.885"		1 Conical	R	2.325"	315	1.080"
Minor	1.050"	0.650"						
4931	1.239"	0.864"	0.785"	1 + damper	R	2.050"	300	1.150"
5019	1.455"	0.810"		1	L	2.430"	190	1.090"

CROW CAMS VALVE SPRINGS Part Number Order

PART NUMBER	O/D	ID OF OUTER	ID OF INNER	SPRING TYPE	RH or LH (OUTER)	FREE LENGTH	SPRING RATE	SOLID HEIGHT
5038	1.211"	0.857"		1 + damper	R	1.750"	340	1.010"
5091	1.495"	1.083"	0.9780"	1 + damper	R	1.940"	348	1.062"
5321	1.334"	1.010"		1	L	1.780"	208	0.940"
5827	1.320"	0.980"		1	R	1.820"	228	0.810"
5828	1.320"	0.980"	0.693"	2	R	1.820"	350	0.900"
5833	1.320"	0.980"	0.760"	2	R	1.820"	300	0.900"
5835	1.325"	0.971"	0.710"	2	R	1.900"	330	0.950"
5838	1.325"	0.978"	0.700"	2	R	1.850"	375	0.900"
5840	1.320"	0.980"	0.710"	2	R	1.820"	308	0.810"
6118	1.344"	1.000"		1	L	2.230"	185	1.050"
6223	1.390"	1.046"		1	R	1.750"	232	0.774"
6336	1.344"	1.000"	0.730"	2	L	2.280"	344	1.050"
6340	1.364"	1.010"	0.735"	2	L	2.100"	400	0.929"
6341								
6434	1.390"	1.046"	0.830"	2	R	1.750"	340	0.775"
6426	1.384"	1.000"	0.810"	2	R	2.170"	240	0.891"
7235	1.435"	1.050"		1	R	1.940"	360	0.845"
7328	1.429"	1.080"	0.810"	2	L	2.280"	290	0.912"
7331	1.430"	1.070"	0.795"	2	L	2.380"	320	1.050"
7332	1.430"	1.070"	0.815"	2	L	2.380"	325	1.050"
7333	1.437"	1.070"	0.810"	2	L	2.380"	330	1.050"
7334	1.455"	1.080"	0.810"	2	L	2.430"	330	1.090"
7347	1.475"	1.080"	0.810"	2	L	2.155"	490	1.145"
7348	1.475"	1.080"	0.810"	2	L	2.155"	480	1.145"
7437	1.470"	1.082"	0.819"	2	L	2.200"	385	1.110"
7450	1.435"	1.050"	0.725"	2	R	1.940"	620	0.845"
7734	1.425"	1.080"	0.810"	2	L	2.280"	280	0.950"
7736	1.437"	1.038"	0.935"	1 + damper	L	2.040"	364	1.100"
7737	1.500"	1.086"	0.966"	1 + damper	L	2.220"	325	1.240"
7738	1.475"	1.060"	0.930"	1 + damper	L	2.155"	350	1.140"
7739	1.414"	1.020"	0.916"	1 + damper	R	2.160"	295	1.150"
7820	1.380"	1.030"		1	R	2.100"	205	0.940"
7937	1.437"	1.070"	0.731"	2 + damper	L	2.380"	325	1.080"
8333	1.515"	1.070"	0.795"	2	L	2.390"	350	1.160"
8335	1.515"	1.130"	0.795"	2	L	2.350"	322	1.115"
8337	1.515"	1.130"	0.795"	2	L	2.350"	375	1.114"
8937	1.530"	1.116"	0.752"	2 + damper	L	2.280"	375	1.130"
8945	1.500"	1.115"	0.800"	2	L	2.360"	460	1.040"
9731	1.539"	1.125"	1.000"	1 + damper	L	2.400"	314	1.180"
9936	1.539"	1.125"	0.760"	2 + damper	L	2.400"	405	1.180"
9941	1.540"	1.045"	0.749"	2 + damper	R	2.325"	440	1.140"
9944	1.550"	1.045"	0.750"	2 + damper	R	2.400"	455	1.115"
9945	1.540"	1.126"	0.697"	2 + damper	L	2.320"	465	1.110"
9946	1.550"	1.130"	0.730"	2 + damper	R	2.420"	554	1.140"
9949	1.550"	1.130"	0.730"	2 + damper	R	2.590"	475	1.320"
9950	1.540"	1.125"	0.731"	2 + damper	L	2.400"	485	1.180"
9954	1.630"	1.188"	0.780"	2 + damper	R	2.350"	565	1.120"
9955	1.550"	1.140"	0.810"	2	R	2.370"	550	1.120"
9961	1.640"	1.190"	0.644"	3	R	2.710"	610	1.216"
10976	1.700"	1.214"	0.641"	3	R	2.450"	735	1.200"