

CROW CAMS VALVE SPRINGS Part Number Order

PART NUMBER	O/D	ID OF OUTER	ID OF INNER	SPRING TYPE	RH or LH (OUTER)	FREE LENGTH	SPRING RATE	SOLID HEIGHT
0513	0.953"	0.697"		1	L	1.937"	132	0.870"
0514	0.838"	0.612"		1	L	1.510"	132	0.710"
0515	1.015"	0.730"		1	L	1.950"	140	0.900"
0606	1.079"	0.770"		1	L	2.140"	176	0.873"
0607	0.910"	0.684"		1	L	1.970"	77	0.750"
0612	1.080"	0.810"		1	R	1.937"	126	0.820"
0613	1.080"	0.796"		1	R	2.230"	130	0.950"
0614	0.970"	0.700"		1	R	2.090"	135	1.030"
0615	1.010"	0.750"		1	L	2.000"	130	0.840"
1025	1.365"	0.735"		1	L	2.100"	250	0.930"
1515	1.000"	0.730"		1	R	1.905"	150	0.895"
1808	1.060"	0.654"		1 Conical	R	1.880"	210	0.885"
minor	0.966"	0.747"		Ovate Wire				
1809	1.060"	0.654"		1 Conical	R	1.950"	210	0.885"
minor	0.966"	0.747"		Ovate Wire				
1832	1.105"	0.754"		1 Conical	R	1.760"	315	0.855"
minor	0.950"	0.585"		Ovate Wire				
2021	1.134"	0.838"		1	R	1.622"	208	0.800"
2834	1.134"	0.838"	0.612"	2	R	1.622"	320	0.750"
2836	1.134"	0.838"	0.612"	2	R	1.622"	340	0.750"
4028	1.275"	0.930"		1	L	1.960"	225	0.880"
4038	1.195"	0.860"		1	R	1.720"	358	0.880"
4162	1.100"	0.775"		1	R	1.870"	280	0.940"
4163	1.160"	0.836"		1	R	1.930"	250	0.930"
4164	1.050"	0.754"		1	R	1.690"	260	0.810"
4174	1.180"	0.865"	0.670"	2	R	1.560"	315	0.800"
4176	1.165"	0.870"	0.660"	2	R	1.870"	340	1.000"
4177	1.105"	0.821"	0.649"	2	R	1.600"	245	0.725"
4220	1.210"	0.926"	0.693"	2	R	1.900"	200	0.820"
4231	1.275"	0.874"		1 Conical	R	2.180"	295	1.090"
Minor	1.051"	0.650"		Ovate Wire				
4235	1.260"	0.872"	0.790"	1 + damper	R	2.150"	354	1.094"
4250	1.214"	0.926"	0.693"	2	R	1.900"	243	0.817"
4326	1.255"	0.930"	0.710"	2	L	2.125"	260	0.865"
4327	1.255"	0.930"	0.684"	2	L	2.135"	275	0.930"
4330	1.280"	0.926"	0.700"	2	R	1.690"	315	0.925"
4334	1.280"	0.950"	0.710"	2	L	2.080"	340	0.950"
4335	1.280"	0.950"	0.684"	2	L	2.030"	355	0.950"
4336	1.275"	0.975"	0.700"	2	L	1.980"	255	0.880"
4406	0.925"	0.625"		1	R	1.560"	250	0.875"
4420	1.436"	1.140"		1 Conical	R	2.310"	366	1.210"
Minor	0.996"	0.700"						
4435	1.210"	1.035"		1 Conical	R	2.180"	358	1.160"
Minor	0.800"	0.630"		Ovate Wire				
4437	1.275"	0.950"	0.684"	2	L	1.780"	374	0.875"
4719	1.255"	0.930"	0.800"	1 + damper	L	2.135"	220	0.930"
4438	1.280"	1.054"	0.684"	2	L	2.250"	369	1.030"
4823	1.282"	0.950"	0.809"	1 + damper	L	2.160"	260	0.930"
4828	1.250"	0.875"		1	L	2.120"	350	1.075"
4830	1.220"	0.860"		1+damper	R	2.080"	310	1.100"
4833	1.250"	0.876"	0.750"	1 + damper	L	1.940"	400	1.010"
4843	1.250"		0.860"	1 + damper	R	2.070"	405	1.160"

CROW CAMS VALVE SPRINGS Part Number Order

PART NUMBER	O/D	ID OF OUTER	ID OF INNER	SPRING TYPE	RH or LH (OUTER)	FREE LENGTH	SPRING RATE	SOLID HEIGHT
4845	1.250"	0.868"	0.787"	1 + damper	R	2.110"	375	1.040"
4918	1.290"	0.885"		1 Conical	R	2.325"	315	1.080"
Minor	1.050"	0.650"						
4931	1.239"	0.864"	0.785"	1 + damper	R	2.050"	300	1.150"
5038	1.211"	0.857"		1 + damper	R	1.750"	340	1.010"
5088	1.385"	0.985"		1	R	2.035"	343	1.200"
5091	1.495"	1.083"	0.9780"	1 + damper	R	1.940"	348	1.062"
5092	1.383"	1.000"		1	R	2.015"	240	1.140"
5825	1.325"	0.970"		1	R	1.900"	248	0.900"
5321	1.334"	1.010"		1	L	1.780"	208	0.940"
5827	1.320"	0.980"		1	R	1.820"	228	0.810"
5828	1.320"	0.980"	0.693"	2	R	1.820"	350	0.900"
5832	1.320"	0.978"	0.760"	2	R	1.850"	322	0.950"
5833	1.320"	0.980"	0.760"	2	R	1.820"	300	0.900"
5835	1.325"	0.971"	0.710"	2	R	1.900"	330	0.950"
5838	1.325"	0.978"	0.700"	2	R	1.850"	375	0.900"
5840	1.320"	0.980"	0.710"	2	R	1.820"	308	0.810"
6118	1.344"	1.000"		1	L	2.230"	185	1.050"
6336	1.344"	1.000"	0.730"	2	L	2.280"	344	1.050"
6340	1.364"	1.010"	0.735"	2	L	2.100"	400	0.929"
6341	1.364"	1.010"	0.735"	2	L	2.100"	388	0.930"
6426	1.384"	1.000"	0.810"	2	R	2.170"	240	0.940"
7328	1.429"	1.080"	0.810"	2	L	2.280"	285	0.912"
7329	1.430"	1.080"	0.810"	2	L	2.280"	292	0.945"
7331	1.430"	1.070"	0.795"	2	L	2.380"	320	1.050"
7332	1.430"	1.070"	0.815"	2	L	2.380"	325	1.050"
7333	1.437"	1.070"	0.810"	2	L	2.380"	330	1.050"
7334	1.455"	1.080"	0.810"	2	L	2.430"	330	1.090"
7347	1.475"	1.080"	0.810"	2	L	2.155"	490	1.145"
7348	1.475"	1.080"	0.810"	2	L	2.155"	480	1.145"
7437	1.470"	1.082"	0.819"	2	L	2.200"	385	1.110"
7733	1.455"	1.070"	0.810"	2	L	2.430"	320	1.090"
7734	1.425"	1.080"	0.810"	2	L	2.280"	280	0.950"
7736	1.437"	1.038"	0.935"	1 + damper	L	2.040"	364	1.100"
7737	1.500"	1.086"	0.966"	1 + damper	L	2.220"	325	1.240"
7738	1.475"	1.060"	0.930"	1 + damper	L	2.155"	350	1.140"
7739	1.414"	1.020"	0.916"	1 + damper	R	2.160"	295	1.150"
7930	1.437"	1.070"	0.700"	2 + damper	L	2.380"	300	1.050"
7937	1.437"	1.070"	0.730"	2 + damper	L	2.380"	325	1.080"
8333	1.515"	1.070"	0.795"	2	L	2.390"	350	1.160"
8335	1.515"	1.130"	0.795"	2	L	2.350"	322	1.115"
8337	1.515"	1.130"	0.795"	2	L	2.350"	375	1.114"
8937	1.530"	1.116"	0.752"	2 + damper	L	2.280"	375	1.130"
8945	1.500"	1.115"	0.800"	2	L	2.360"	460	1.040"
9731	1.539"	1.125"	1.000"	1 + damper	L	2.400"	314	1.180"
9936	1.539"	1.125"	0.760"	2 + damper	L	2.400"	405	1.180"
9941	1.540"	1.045"	0.749"	2 + damper	R	2.325"	440	1.140"
9945	1.540"	1.126"	0.697"	2 + damper	L	2.320"	465	1.110"
9946	1.550"	1.130"	0.730"	2 + damper	R	2.420"	554	1.140"
9950	1.540"	1.125"	0.731"	2 + damper	L	2.400"	485	1.180"
9955	1.550"	1.140"	0.810"	2	R	2.370"	550	1.120"
9961	1.640"	1.190"	0.644"	3	R	2.710"	610	1.216"

