

# VALVE TRAIN ACCESSORIES

## Valve Spring Cups

PART NO	O/D	SPRING O.D.	BORE	PART NO	O/D	SPRING O.D.	BORE
VSC460	1.585"	1.450"	0.560"	VSC560	1.685"	1.560"	0.570"
VSC480	1.585"	1.450"	0.650"				

## Valve Spring Seats. Guide hole can be drilled to suit application

PART NO	O/D	SPIGOT DIAM.	SPIGOT HEIGHT	BORE	BASE Thickness
VSS1251	1.28"	.670"	0.080"	0.50"	0.045"
VSS1258	1.28"	.880"	0.080"	0.50"	0.045"
VSS1451	1.44"	1.08"	0.050"	0.50"	0.090"
VSS1452	1.44"	0.790"	0.080"	0.50"	0.060"
VSS1456	1.44"	0.790"	0.080"	0.57"	0.050"

## Valve Spring Shims Most shims available in .060"(A) .030"(B) and .015"(C) thick.

PART NO	O.D.	I.D.	PART NO	O.D.	I.D.	PART NO	O.D.	I.D.
VS250	1.250"	0.500"	VS437	1.437"	0.500"	VS739	1.500"	0.645"
VS203	1.250"	0.812"	VS438	1.437"	0.562"	VS103	1.500"	1.031"
VS256	1.250"	0.562"	VS306	1.437"	0.645"	VS510	1.510"	0.570"
VS102	1.360"	1.000"	VS305	1.437"	0.765"	VS601	1.640"	0.635"
VS200	1.360"	0.640"	VS303	1.480"	0.700"	VS740	1.640"	0.650"

## Valve Stem Seals \*Severe duty seals colour coded

PART NO.	VALVE STEM	GUIDE DIAM.	PART NO.	VALVE STEM	GUIDE DIAM.	PART NO.	VALVE STEM	GUIDE DIAM.
S2*	.343"	.530"	S7*	.343"	.500"	S9	.315"	.562"

## Pushrod Guide Plates

PART NO.	APPLICATION	DIAM.	PART NO.	APPLICATION	DIAM.
GP186	Holden 6. 186,202	5/16"	GP308	Holden 308	5/16"
GP350	Chev 350 Stepped	5/16"	GP304	Holden EFI V8	5/16"
GP302	Ford 302W	5/16"	GP351	Ford 351C	5/16"

## Valve Stem Lash Caps (0.080" thick)

PART NO.	DIMENSIONS	APPLICATION
31201	5/16" valve 0.312"	Early Falcon 6, Ford 1500
34301	11/32" valve 0.343"	Holden, Chev SB, Ford 302-351
37501	3/8", valve 0.375"	Chev B/B, Chrysler, Ford FE 390