

VALVE TRAIN ACCESSORIES

Valve Spring Cups

| PART NO | O/D | SPRING O.D. | BORE | PART NO | O/D | SPRING O.D. | BORE |
|---------|--------|-------------|--------|---------|--------|-------------|--------|
| VSC460 | 1.585" | 1.450" | 0.560" | VSC560 | 1.685" | 1.560" | 0.570" |
| VSC480 | 1.585" | 1.450" | 0.650" | | | | |

Valve Spring Seats. Guide hole can be drilled to suit application

| PART NO | O/D | SPIGOT DIAM. | SPIGOT HEIGHT | BORE | BASE Thickness |
|---------|-------|--------------|---------------|-------|----------------|
| VSS1251 | 1.28" | .670" | 0.080" | 0.50" | 0.045" |
| VSS1258 | 1.28" | .880" | 0.080" | 0.50" | 0.045" |
| VSS1451 | 1.44" | 1.08" | 0.050" | 0.50" | 0.090" |
| VSS1452 | 1.44" | 0.790" | 0.080" | 0.50" | 0.060" |
| VSS1456 | 1.44" | 0.790" | 0.080" | 0.57" | 0.050" |

Valve Spring Shims Most shims available in .060"(A) .030"(B) and .015"(C) thick.

| PART NO | O.D. | I.D. | PART NO | O.D. | I.D. | PART NO | O.D. | I.D. |
|---------|--------|--------|---------|--------|--------|---------|--------|--------|
| VS250 | 1.250" | 0.500" | VS437 | 1.437" | 0.500" | VS739 | 1.500" | 0.645" |
| VS203 | 1.250" | 0.812" | VS438 | 1.437" | 0.562" | VS103 | 1.500" | 1.031" |
| VS256 | 1.250" | 0.562" | VS306 | 1.437" | 0.645" | VS510 | 1.510" | 0.570" |
| VS102 | 1.360" | 1.000" | VS305 | 1.437" | 0.765" | VS601 | 1.640" | 0.635" |
| VS200 | 1.360" | 0.640" | VS303 | 1.480" | 0.700" | VS740 | 1.640" | 0.650" |

Valve Stem Seals *Severe duty seals colour coded

| PART NO. | VALVE STEM | GUIDE DIAM. | PART NO. | VALVE STEM | GUIDE DIAM. | PART NO. | VALVE STEM | GUIDE DIAM. |
|----------|------------|-------------|----------|------------|-------------|----------|------------|-------------|
| S2* | .343" | .530" | S7* | .343" | .500" | S9 | .315" | .562" |

Pushrod Guide Plates

| PART NO. | APPLICATION | DIAM. | PART NO. | APPLICATION | DIAM. |
|----------|-------------------|-------|----------|---------------|-------|
| GP186 | Holden 6. 186,202 | 5/16" | GP308 | Holden 308 | 5/16" |
| GP350 | Chev 350 Stepped | 5/16" | GP304 | Holden EFI V8 | 5/16" |
| GP302 | Ford 302W | 5/16" | GP351 | Ford 351C | 5/16" |

Valve Stem Lash Caps (0.080" thick)

| PART NO. | DIMENSIONS | APPLICATION |
|----------|---------------------|---------------------------------|
| 31201 | 5/16" valve 0.312" | Early Falcon 6, Ford 1500 |
| 34301 | 11/32" valve 0.343" | Holden, Chev SB, Ford 302-351 |
| 37501 | 3/8", valve 0.375" | Chev B/B, Chrysler, Ford FE 390 |