

VALVE SPRINGS

VALVE SPRINGS PART NUMBER ORDER

Part Number	O/D	ID of Outer	ID of Inner	Spring Type	RH or LH (Outer)	Free Length	Spring Rate (lb/in)	Solid Height
507	1.000"	0.760"		1	L	2.050"	75	0.750"
511	0.937"	0.697"		1	L	1.490"	123	0.740"
513	0.953"	0.697"		1	L	1.937"	132	0.930"
514	0.838"	0.612"		1	L	1.500"	145	0.710"
515	1.015"	0.725"		1	L	2.165"	155	1.060"
607	0.910"	0.684"		1	L	1.970"	80	0.780"
612	1.090"	0.810"		1	R	2.055"	120	0.880"
613	1.080"	0.796"		1	R	2.230"	130	1.000"
615	1.015"	0.740"		1	L	2.000"	135	0.870"
1025	1.370"	1.005"		1	L	2.110"	265	1.030"
1511ML	1.050" TOP 1.295" BOT	0.643" TOP 0.908" BOT		1 Conical	R	2.180"	385	1.100"
1804	0.995" TOP 1.060" BOT"	0.635" TOP 0.700" BOT		1 Conical	R	2.060"	280	1.020"
1808	0.970" TOP 1.060" BOT	0.650" TOP 0.727" BOT		1 Conical	R	1.970"	220	0.880"
1809	0.970" TOP 1.060" BOT	0.650" TOP 0.740" BOT		1 Conical	R	2.180"	205	0.900"
1832	0.970" TOP 1.105" BOT	0.585" TOP 0.745" BOT		1 Conical	R	1.810"	310	0.900"
2021	1.140"	0.380"		1	R	1.650"	235	0.750"
2834 ^D	1.140"	0.830"	0.612"	2	R	1.650"	390	0.830"
2836 ^D	1.140"	0.830"	0.612"	2	R	1.650"	355	0.830"
4021	1.065" TOP 1.255" BOT	0.670" TOP 0.875" BOT		1 Conical	R	1.960"	350	1.190"
4028	1.250"	0.920"		1	L	2.105"	190	0.950"
4038	1.200"	0.860"		1	R	1.830"	380	0.920"
4162	1.100"	0.765"		1	R	1.895"	260	0.980"
4163	1.160"	0.835"		1	R	1.980"	260	0.975"
4164	1.050"	0.735"		1	R	1.740"	265	0.840"
4177 ^D	1.113"	0.805"	0.636"	2	R	1.660"	230	0.730"
4207X ^D	1.304"	0.950"	0.680"	2	R	2.300"	430	1.000"
4209X ^D	1.324"	0.950"	0.689"	2	R	2.230"	495	1.000"
4220 ^D	1.210"	0.926"	0.700"	2	R	1.900"	200	0.820"
4231	1.045" TOP 1.275" BOT	0.650" TOP 0.870" BOT		1 Conical	R	2.260"	300	1.100"
4250 ^D	1.212"	0.930"	0.695"	2	R	1.960"	250	0.805"
4320	1.245"	0.910"		1	L	2.105"	210	0.950"
4326 ^D	1.240"	0.920"	0.685"	2	L	2.100"	275	0.950"
4327 ^D	1.255"	0.930"	0.690"	2	L	2.170"	270	0.940"
4328 ^D	1.245"	0.920"	0.685"	2	L	2.165"	260	0.940"

Note: Springs marked with xxxx-xx^D denotes that it is a double spring.

VALVE SPRINGS PART NUMBER ORDER

Part Number	O/D	ID of Outer	ID of Inner	Spring Type	RH or LH (Outer)	Free Length	Spring Rate (lb/in)	Solid Height
4330 ^D	1.280"	0.926"	0.700"	2	R	1.960"	315	0.925"
4334 ^D	1.280"	0.950"	0.710"	2	L	2.130"	340	0.950"
4335 ^D	1.280"	0.950"	0.684"	2	L	2.170"	355	0.950"
4336 ^D	1.245"	0.920"	0.685"	2	L	2.100"	295	0.920"
4403	1.000"	0.700"		1	R	1.900"	260	0.945"
4420	1.110" TOP 1.440" BOT	0.660" TOP 0.990" BOT		1 Conical	R	2.445"	360	1.200"
4429 ^D	1.167"	0.860"	0.660"	2	R	1.820"	240	0.810"
4435	1.060" TOP 1.200" BOT	0.640" TOP 0.800" BOT		1 Conical	R	2.220"	350	1.150"
4437 ^D	1.255"	0.920"	0.684"	2	L	2.100"	305	0.875"
4438 ^D	1.290"	0.948"	0.690"	2	R	2.345"	365	1.050"
4439 ^D	1.305"	0.950"	0.690"	2	R	2.300"	375	1.020"
4511X	1.035" TOP 1.290" BOT	0.665" TOP 0.910" BOT		1 Conical	R	2.230"	365	1.100"
4718	1.255"	0.920"	0.835"	1 + Damper	L	2.100"	230	0.930"
4719	1.240"	0.920"	0.840"	1 + Damper	L	2.090"	250	0.930"
4823	1.275"	0.930"	0.850"	1 + Damper	L	2.170"	275	0.960"
4828	1.250"	0.870"		1	R	2.030"	360	1.080"
4830	1.220"	0.860"	0.755"	1 + Damper	R	2.140"	310	1.120"
4833	1.255"	0.868"	0.780"	1 + Damper	R	2.030"	415	1.100"
4835	1.220"	0.860"	0.765"	1 + Damper	R	2.170"	340	1.090"
4836	1.250"	0.875"	0.780"	1 + Damper	R	2.040"	405	1.080"
4843	1.265"	0.875"	0.760"	1 + Damper	R	2.015"	411	1.160"
4845	1.260"	0.880"	0.785"	1 + Damper	R	2.130"	380	1.140"
4910 ^D	1.550"	1.150"	0.800"	2	R	2.460"	555	1.110"
4918	1.040" TOP 1.275" BOT	0.640" TOP 0.875" BOT		1 Conical	R	2.335"	314	1.090"
4920 ^D	1.560"	1.110"	0.780"	2	R	2.475"	620	1.180"
4931	1.230"	0.880"	0.770"	1 + Damper	R	2.020"	275	1.140"
4936	1.230"	0.875"	0.780"	1 + Damper	R	2.000"	330	1.120"
5002	1.510"	1.090"	0.970"	1 + Damper	L	2.200"	345	1.300"
5014	1.420"	1.010"		1	L	2.145"	310	1.250"
5037	1.230"	0.875"		1	R	2.060"	265	1.230"
5038	1.211"	0.857"		1	R	1.780"	340	1.010"

VALVE SPRINGS PART NUMBER ORDER

Part Number	O/D	ID of Outer	ID of Inner	Spring Type	RH or LH (Outer)	Free Length	Spring Rate (lb/in)	Solid Height
5077	1.500"	1.080"	0.990	1 + Damper	R	1.960"	355	1.095"
5078^D	1.332"	0.990"	0.715	2	L	1.835"	330	1.070"
5080	1.283"	0.930"		1	R	1.750"	240	0.930"
5088	1.375"	0.960"		1	R	2.050"	335	1.200"
5091	1.500"	1.080"	0.99	1 + Damper	R	1.960"	355	1.095"
5092	1.390"	1.000"		1	R	2.035"	245	1.120"
5094	1.420"	1.000"		1	L	2.120"	350	1.265"
5107	1.330"	0.960"		1	R	1.920"	230	0.930"
5825	1.330"	0.960"		1	R	1.935"	230	0.950"
5827	1.330"	0.980"		1	R	1.860"	228	0.840"
5828^D	1.330"	0.980"	0.660"	2	R	1.860"	350	0.840"
5833^D	1.330"	0.990"	0.760"	2	R	2.160"	330	0.900"
5835^D	1.330"	0.971"	0.720"	2	R	1.920"	335	0.950"
5838^D	1.330"	0.980"	0.690"	2	R	1.930"	395	0.950"
5840^D	1.335"	1.000"	0.720"	2	R	1.930"	345	0.860"
5844-IRH	0.950"	0.720"		1	R	1.955"	95	0.750"
5854^D	1.335"	0.980"	0.690"	2	R	1.960"	410	0.900"
6038	1.255"	0.900"		1	R	2.050"	340	1.170"
7328^D	1.425"	1.095"	0.820"	2	L	2.380"	280	0.960"
7329^D	1.435"	1.075"	0.800"	2	L	2.400"	285	0.945"
7331^D	1.450"	1.090"	0.800"	2	L	2.350"	330	1.100"
7332^D	1.445"	1.090"	0.800"	2	L	2.335"	315	1.050"
7333^D	1.450"	1.090"	0.820"	2	L	2.345"	330	1.050"
7334^D	1.455"	1.080"	0.810"	2	L	2.440"	320	1.050"
7335	1.465"	1.070"		1	L	2.410"	285	1.040"
7341^D	1.470"	1.080"	0.800"	2	L	2.280"	430	1.050"
7342^D	1.460"	1.080"	0.800"	2	L	2.280"	390	1.040"
7437^D	1.465"	1.080"	0.800"	2	L	2.260"	380	1.050"
7733^D	1.465"	1.085"	0.790"	2	L	2.470"	320	1.030"
7734^D	1.425"	1.080"	0.800"	2	L	2.400"	280	1.000"
7736	1.445"	1.040"	0.955"	1 + Damper	L	2.040"	340	1.100"

Note: Springs marked with xxxx-xx^D denotes that it is a double spring.

VALVE SPRINGS **PART NUMBER ORDER**

Part Number	O/D	ID of Outer	ID of Inner	Spring Type	RH or LH (Outer)	Free Length	Spring Rate (lb/in)	Solid Height
7737	1.510"	1.086"	0.965"	1 + Damper	L	2.220"	345	1.310"
7738	1.470"	1.060"	0.960"	1 + Damper	L	2.170"	350	1.180"
7739	1.420"	1.015"	0.925"	1 + Damper	R	2.160"	340	1.150"
7930 ^D	1.460"	1.000"	.690"	2 + Damper	L	2.360"	350	1.070"
7937 ^D	1.465"	1.000"	0.720"	2 + Damper	L	2.360"	350	1.080"
8333 ^D	1.515"	1.120"	0.800"	2	L	2.480"	350	1.210"
8335 ^D	1.515"	1.120"	0.795"	2	L	2.480"	322	1.210"
8337 ^D	1.515"	1.120"	0.800"	2	L	2.350"	360	1.114"
8937 ^D	1.530"	1.120"	0.760"	2 + Damper	L	2.335"	390	1.180"
9731	1.550"	1.125"	1.000"	1 + Damper	L	2.460"	320	1.180"
9936 ^D	1.539"	1.120"	0.765"	2 + Damper	L	2.460"	400	1.180"
9941 ^D	1.540"	1.025"	0.740"	2 + Damper	R	2.380"	440	1.140"
9945 ^D	1.560"	1.010"	0.690"	2 + Damper	L	2.475"	460	1.200"
9950 ^D	1.540"	1.130"	0.725"	2 + Damper	L	2.430"	485	1.150"

Note: Springs marked with xxxx-xx^D denotes that it is a double spring.